



# CMC Premium Release SB

VOC Compliant Form Release Agent

## Description

CMC Premium Release SB multi-reactive form release is composed of an organic chemical that reacts with the alkali content of concrete to form a release film that effectively inhibits the bonding of the concrete to the form. In addition, the product also contains a high molecular weight, nonreactive, chemically inert ingredient to assist in clean, quick form release and removal. These exclusive ingredients combine the effectiveness of a chemically reactive type and an inert barrier type to provide a doubly effective separation and the ultimate in form release.

## Uses

CMC Premium Release SB can be used on forms such as wood, steel, aluminum, fiberglass-reinforced, all grades of plywood (pre-oiled, overlaid, LDO, NDO, HDO), epoxy-coated, and urethane-coated, as well as fiber tubes. DO NOT USE on expanded polystyrene (foam), rubber, latex, or latex forms made from SBR or natural rubber. Wood forms should be saturated prior to first use.

CMC Premium Release SB increases the life of wood forms by penetrating into the wood to waterproof and prevent deterioration. It also reduces maintenance requirements on metal forms by forming a rustproof film that makes the metal form essentially self-cleaning and rust-free. CMC Premium Release SB should be applied to fiber tube forms even though they may be pre-coated. Tubes will strip much easier, even 60 to 90 days later. If tubes are stripped in 5 to 10 days, hand rubbing is greatly facilitated when tubes are coated with CMC Premium Release SB.

CMC Premium Release SB also cuts machine cleanup time because it minimizes concrete buildup. Pavers, trucks, mixers, spreader-finishers, buggies, chutes, and other types of equipment should be sprayed daily with CMC Premium Release SB for easy cleanup and rust prevention.

CMC Premium Release SB can be applied on forms for prestressed and precast concrete to produce a better and cleaner cast. The product will not stain or discolor concrete. CMC Premium Release SB is also available in a true waterbased formula, CMC Premium Release WB.

## Features & Benefits

- Provides a better and cleaner cast when applied on prestressed and precast concrete forms.
- Cuts stripping time to an absolute minimum.
- Reduces form cleaning and repairing.
- Increases wood form life, prevents rust, and rustproofs metal forms.
- Effectively minimizes concrete buildup on pavers, R/M trucks, mixers, spreader-finishers, buggies, chutes, and other equipment.
- Prevents bonding between poured concrete and the form.
- Breaks concrete bond between the surface and the form cleanly and effectively, leaves smooth surface.
- Will not stain or discolor concrete and can be painted over.
- Ready to use, requires no additional mixing.
- VOC compliant.

## Directions For Use

**Surface Preparation:** Clean form surfaces thoroughly prior to application. Remove all rust, scale, and/or previously used form release agents from the forms in accordance with good concrete practices. It is imperative when using new wooden forms of all types (plain wooden, plywood, rough cut, etc.) that CMC Premium Release SB be applied and reapplied until complete saturation has been accomplished prior to first use.

**Application Methods:** Spraying is the ideal method of application. Use a Chapin 1-5915 spray nozzle that produces a flow of 1/10 of one gallon per minute. CMC Premium Release SB may also be applied by roller coating, mopping, or brushing. A thin film should be applied for maximum economy and efficiency. Runs or

*Continued on reverse side*

puddles need to be brushed out. For metal forms, the best results are obtained with a spray-on “fog” application of CMC Premium Release SB.

### Technical Data

Freezing point.....Less than 10°F (-12°C)  
Color.....Amber  
Staining.....None

### Packaging

5 Gallon (18.93 Liter) Pails  
55 Gallon (208.20 Liter) Drums.

### Coverage

600 - 1500 ft.2/gal. (14.7 - 36.8 m2/L), depending on type and porosity of the form surface.

### Shelf Life

When stored indoors and in original, unopened containers at temperatures between 40 - 90°F (4 - 32°C), shelf life is a minimum of two years from date of manufacture.

### Specifications

Complies with all current federal, state, and local maximum allowable VOC requirements, including U.S. EPA, LADCO, SCAQMD, and OTC.

### Precautions

For exterior use only. DO NOT OVER-APPLY CMC PREMIUM RELEASE SB TO FORMS AND EQUIPMENT. DO NOT DILUTE. DO NOT USE ON expanded polystyrene (foam), rubber, latex (or latex forms made from SBR or natural rubber), or plastercoated forms. Read and follow application information and precautions. Product is an eye, skin, and respiratory irritant. Refer to Safety Data Sheet for complete health and safety information.

### LEED Information

May help contribute to LEED credits:

- IEQ Credit 4.2: Low-Emitting Materials: Paints and Coatings
- MR Credit 2: Construction Waste Management
- MR Credit 4: Recycled Content
- MR Credit 5: Regional Materials

**DISCLAIMER:** The information contained herein is included for illustrative purposes only, and to the best of our knowledge, is accurate and reliable. We cannot however under any circumstances make any guarantee of results or assume any obligation or liability in connection with the use of this information. As we have no control over the use to which others may put its product, it is recommended that the products be tested to determine if suitable for specific application and/ or our information is valid in a particular circumstance. Responsibility remains with the architect or engineer, contractor and owner for the design, application and proper installation of each product. Specifier and user shall determine the suitability of products for specific application and assume all responsibilities in connection therewith.